




Rec'd PCT/PTO 10 MAR 2005
CT/GB 2003 / 0 0 3 8 6 3



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

[Signature]


Dated

6 February 2004

Patents Act 1977
(Rule 16)



The
Patent
Office



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

573GB

14SEP02 E748085-1 D02651

2. Patent application number

(The Patent Office will fill in this part)

P01/7700 0.00-0221255.3 ACCOUNT CHA

0221255.3

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Renishaw plc
New Mills
Wotton-under-Edge
Gloucestershire, GL12 8JR

Patents ADP number (*if you know it*)

2691002

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

2691002

4. Title of the invention

Touch Probe

5. Name of your agent (*if you have one*)

M J Fowler et al

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)

Renishaw plc, Patent Department
New Mills
Wotton-under-Edge
Gloucestershire, GL12 8JR

Patents ADP number (*if you know it*)

2691003

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country

Priority application number
(*if you know it*)

Date of filing
(*day / month / year*)

-

-

-

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(*day / month / year*)

-

-

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Yes

TOUCH PROBE

The present invention relates to touch probes.

5 Touch probes which have a stylus which is mounted in a seat within the probe and is biased into the seat are known. When the stylus contacts a surface, through relative movement of the probe and the surface, the stylus is deflected from its seat against the action of
10 the bias and this movement generates a signal which is passed to the machine so the machine can record the instantaneous position of the probe/surface.

The surface may belong to a workpiece whose dimensions
15 are being measured or, to a tool which is used to shape a workpiece thus enabling adjustments, to take into account tool wear, to be made to a machine cycle.

In order to make accurate measurements, the stylus
20 needs to be seated in a repeatable location within the probe called the neutral position. This can be achieved by supporting the stylus in a kinematic seat. An example of such a kinematic seat is described in US 4,153,998 in which, the stylus is supported by three
25 radially extending arms spaced at 120° around the axis of the stylus. The arms are supported on v notches produced by pairs of closely spaced balls which are fixed to the probe. A spring biases the arms into the v notches. The balls and arms form part of a circuit
30 which is broken when the stylus is deflected. In an alternate measurement method, instead of using the kinematic seat itself to detect deflections, strain gauges may be located so as to detect movement from the neutral position. This is described in US 4,462,162.

If the probe stylus is deflected and released suddenly, for example during a crash of the stylus into a surface or perhaps, a manual movement of the probe, the movement of the stylus with respect to the probe can cause shock loading of the kinematic seat when the stylus is biased back to the seated position by the spring. This can damage fragile parts of the measuring circuit.

10

According to the present invention there is provided a touch probe including

first locating elements within the probe;

second locating elements on a stylus holder which co-operate with the first locating elements to locate the stylus holder within the probe; and

a bias to urge the first and second locating elements into contact, characterised in that,

a damper is provided between the probe and the stylus holder.

20

Preferably, the first locating elements each comprise a pair of balls which provide a v shaped seat and the second locating elements each comprise a roller which supports the stylus on the seat.

25

In a preferred embodiment the damper is an insert which slows the return movement of the first and second locating elements to the located or neutral position.

30

Alternatively, the damper is an energy absorbing insert. An example is an insert made from a material which exhibits hysteresis for example a rubber.

The invention will now be described, by way of example, with reference to the accompanying drawings, of which:

Figure 1 is a cross-sectional view of a probe according to the invention,

5 Figure 2 is a cross-section on the line II-II of figure 1, of an assembled probe,

Figure 3 is a cross-sectional view of a probe having an alternative insert according to the invention,

10 Figure 4 is a cross-sectional view of an alternative probe according to the invention,

Figure 5 is a cross-sectional view of an insert according to the invention.

15 Figures 1 and 3 show a probe 10 having an outer housing 12, preferably made of steel, and which has a radially inwardly directed annular flange 14. Mounted within the housing 12 is a stylus holder 16 to which a stylus (not shown) may be connected.

20 The stylus holder 16 protrudes from the housing 12 through an opening 20 for connection of a stylus and contacting of a workpiece or tool when relative movement takes place between the probe and the
25 workpiece or tool.

Six recesses 22 are formed in the flange 14 and are open in the direction facing away from the opening 20. The recesses are arranged in pairs, and the pairs are
30 spaced apart at 120° around the longitudinal axis of the probe 18A. The recesses are adapted to receive balls 20, and may be of any convenient shape for example conical or triangular, whereby when the ball is received in the recess it remains in a stable position

and is kinematically supported. The spacing of the balls within each pair is such that they may be bridged by, and form a stable seating for, a roller 24 carried by the stylus holder 16. \

5

The rollers 24 are fitted in holes 26 in the stylus holder spaced at 120° around the axis 18A, and the holes are initially lined with a plastic insert 28, which may be split along its length, and into which the rollers
10 are pressed.

The balls are both located and clamped into their respective recesses by means of an open-ended cylindrical plug 30 made out of hard plastic. In the
15 annular surface at its open end, the plug has six appropriately spaced recesses 32, which in the assembled probe, fit over the balls. Also, at its open end, the plug 30 is formed with three elongate slots 34 which act as guides for the rollers 24 as the stylus
20 holder tilts and is moved vertically by forces acting on the end of the stylus.

The stylus holder is biased into a neutral position, when no force is applied to the stylus, by means of a
25 spring 36 which produces a force in the direction of the axis 18A to urge the rollers into the seats formed between the balls 20.

In order to enable the probe to produce a signal when
30 the stylus is deflected either by tilting or vertical movement, the balls are electrically connected in series to form a circuit which is completed by the rollers making contact with both balls in each pair.

The balls are made from a hard electrically conducting material, for example steel or tungsten carbide, and they must therefore be insulated from the housing 12 where they make contact with the housing in the
5 recesses 22. This is achieved using a thin flexible electrically conductive element 40 made of two layers. The first layer 42 is formed from an insulating material, and the second layer 44 is part-annular and formed from an electrically conductive material.

10

When the probe is assembled, the annular thin element is positioned on the annular flange 14 with its insulating side in contact with the conducting areas of the recesses 22. Two contact pins 46 contact opposite
15 ends of the circuit completed by the balls, rollers and thin flexible element and, at their distal end, enable access to the circuit from outside the probe. The balls are received in the recesses 22 in the flange 14 and in the recesses 32 in the plug. The balls are
20 electrically insulated from the flange by the thin flexible element 40. The thin flexible element 40 is deformed by the kinematically located balls. Various embodiments of this flexible element are described in EP0967455.

25

Referring now to figure 1, the plug 30 has a downwardly extending central portion 31 which lies inside the spring 36. The central portion 31 has a recess 33 in which one end of a plastic insert 35 is slidably
30 housed. The other end of the insert 35 is located within a recess 17 of the stylus holder 16 at the distal end of the stylus holder to that which protrudes from the opening 20 of the housing. Each end of the insert 35 has a flange which has a substantially

similar diameter to the recess in which it is housed. The recess 17 in the stylus holder 16 has a lip 19 which prevents the insert 35 from being removed from stylus recess 17.

5

On a stylus deflection, the stylus holder 16 moves against the spring 36 pushing the insert 35 into the recess 33 of the plug 30 (and to a lesser degree into the stylus recess 17). When the force is removed, the
10 spring 36 urges the stylus holder 16 back into its neutral position. The insert 35 resists the action of the spring 36 slowing the return of the stylus holder to its neutral position thus preventing damage, in this case, to the thin flexible element 40.

15

The flanges on each end of the insert 35 may be formed integrally with the rest of the insert or, for example from plastic skirts that are glued onto the insert. The insert may be made from any suitable plastic
20 material, such as polypropylene, which is flexible enough to slide within the recess during a stylus deflection but stiff and tough enough that the flanges do not deform excessively or tear during the return of the stylus holder to its neutral position. The flanges
25 form a seal in each recess 17, 33. If the seal is too complete then air would not be able to bleed around the edge of each flange thus preventing the spring 36 from returning the stylus holder to its neutral position. The flanges may thus be formed so as to provided bleed
30 zones around their circumference or alternatively, one or more bleed holes 37 may be provided. The use of bleed holes is preferred as the air flow may be controlled with greater accuracy.

Referring now to figure 3 which shows a probe 10 having an alternative insert 50. Insert 50 is manufactured from a material which exhibits hysteresis, in this case a fluorocarbon rubber. Rubbers which have large side chains exhibit greater losses than those with smaller side chains. The insert 50 is partially housed, at one end, within recess 33 of plug 30. At the other end, is a nipple 52 which just contacts the stylus holder 16 when the stylus holder is in its neutral position.

10 This ensures that the kinematic location is substantially unaffected by the presence of the insert 50 and that the insert 50 has maximum energy absorbing effect when the stylus is triggered.

15 On a stylus (not shown) deflection, the stylus holder will tilt and/or move in the vertical (z) direction. The insert 50 is compressed by this movement and absorbs the energy. As the insert 50 is made from a rubber, it exhibits hysteresis i.e. the compression of the rubber uses more energy than is released on

20 subsequent relaxation of the rubber (the difference is mainly converted to heat). This effect may be enhanced by the use of a filler within the rubber. One suitable filler is carbon powder which converts some of the residual compression energy into heat as the

25 compression of the rubber causes friction between different carbon powder particles. A suitable amount of carbon is between 10 and 120 parts per hundred of resin (ppr) and is preferably between 20 and 100 ppr.

30 The compression of the rubber inset 50 absorbs energy which would have otherwise compressed the spring 36. This means that there is less kinetic energy when the spring returns the stylus holder 16 to its neutral position. As the insert 50 converts a high proportion

of the energy that it has removed from the system into heat (as it is lossy), it only contributes a small proportion of energy into returning the stylus holder to its neutral position thus, the impact of the rollers 24 on the balls 20 and thus on the flexible element 40 is reduced. Certain rubber materials have the extra benefit that they recover from a compression at a slow rate thus the release of this energy has a minimal, if any, contribution to the effect of releasing the spring and enabling the stylus holder to return to the neutral position. An example of such a rubber is Sorbothane. This not only reduces normal wear and tear on the probe parts, but can also prevent damage in an abnormal situation such as a crash of the stylus into an object.

The heat generated by the insert during deflections is not sufficient to cause any thermal distortions of the kinematic location or the probe or stylus. A heat sink, such as oil, could be used within the probe cavity to minimise such a risk and this would have the added advantage that the oil, being of higher viscosity than air, would aid the damping process.

The insert 50 could be replaced by a rubber ball. The geometry of the downwardly extending portion 31 of plug 30 would need to be changed in order to seat the ball correctly.

The insert or ball 50 need not contact the stylus holder at all times. This would ensure that the kinematic location were not in any way being affected by the damper. There could even be a gap between the insert and the stylus holder which may correspond to the size of a normal deflection for that particular

probe, so the damping effect would then only be used in exceptional circumstances. This of course would reduce the effectiveness of a particular insert as it cannot absorb energy until it is being compressed and would
5 also require that that insert were securely fixed in the recess to prevent removal therefrom during normal use of the probe.

The person skilled in the art will appreciate that a
10 number of different materials show a hysteresis effect and that the proportion of energy absorbed is a function of the material used as well as any additives and the conditions of use. So, an insert can be
15 tailored to suit particular circumstances without use of more than known material properties.

Figure 4 is a cross-sectional view of an alternative probe 50 having a housing 52. A stylus holder 54 is kinematically located within the probe by three arms 56
20 which sit in v shaped grooves formed by three pairs of balls 58. The pairs of balls 58 are mounted in the outer ring 60 of a central boss 62. Three webs 64 of material of reduced thickness connect the outer ring 60 to the central boss 62. The central boss 62 is rigidly
25 fixed to the probe housing 52. Located on each of the webs 64, is a strain gauge 66. The arms 56 of the stylus holder 54 are biased into contact with the v shaped grooves by a coil spring 68 which is retained in position within the probe housing 52 by a plastic plug
30 70. A damping insert 76 is retained within the spring 68 by, at a first end, a recess 74 in a downwardly extending portion 72 of the plastic plug 70 and, at the other end, by a recess 78 in the stylus holder 54.

When a stylus is deflected, the stylus holder 54 moves within the probe housing 52 against the action of the spring 68. The movement is detected by the strain gauges 66 as any change in loading on the outer ring 60 causes flexure of the thin webs of material 64. The webs of material 64 are each located between two pairs of balls 58 making the strain gauges more sensitive to tilting movements. The signals from the strain gauges 66 are relayed back to a machine controller or machine interface via two contact pins 79 which provide electrical connection to the strain gauges.

In order to make the probe as sensitive and thus as accurate as possible, the webs of material 64 are as thin and narrow as possible. This however can lead to damage of the strain gauges as movement of the outer ring 60 with respect to the central boss 62 is magnified as the cross sectional area of the webs 64 is reduced. The probability of damaged is increased when either high speed measurements are taking place or if the probe crashes into a surface.

To reduce the possibility of strain gauge damage, a damper, in the form of a plastic insert 76 is used to slow down the return movement of the stylus holder 54 to its neutral, or kinematically located position. The insert has a triangular profiled flange at each end which allows easy movement of the flange into its respective recess 74, 78 i.e. when there has been a stylus deflection and the spring 68 is being compressed. However, when the deflecting force is removed and the spring bias towards the neutral position returns, the flanges of the insert 76 resist this return movement resulting in a reduction in the

speed and force of the return to the neutral position by the spring. So, if there has been a large stylus (and thus stylus holder) deflection or a high force impact the efficiency of the spring in returning the stylus holder to the neutral position is reduced.

Figure 5 is a cross-sectional view of a further insert according to the invention. A first end 92 of the insert 90 is slidably housed in a recess 84 within a downwardly extending portion 82 of a plastic plug 80 which is use would be housed within a probe (not shown). This first end 92 of the insert 90 has a flange which resists downward motion of the insert with respect to the recess 84. A second end of the insert 90 is a ball 94. The ball 94 is housed within a ball joint cavity 96 of a stylus holder 88.

In kinematic positioning of one object with respect to another as described above, it is preferable that friction between the two parts of the kinematic joint is kept to a minimum. This means that forces that do not act along the longitudinal axis of the probe should be kept to a minimum. The use of a ball joint at one end of the insert enables smooth motion of the stylus holder with respect to the probe in a plane perpendicular to the probe axis. This assists not only as regards repeatability of the kinematic joint, but also by providing less resistance to off axis movement such as tilting of the stylus holder within the probe cavity thus helping to retain probe sensitivity.

The type of insert used within a probe is function of the type of probe and stylus and their characteristics. Some styli are designed to be contacted mainly in the x

and y planes for example, a square or disc shaped stylus. In this case, the amount of overtravel required in the z-direction within the probe is limited as stylus deflections are generally in the xy plane.

- 5 In this situation, either an energy absorbing insert or an insert that control the return movement to the seated position can be utilised. Overtravel is the space within the probe in which the stylus holder may move in the z-direction before contacting a part of the
- 10 inside of the probe. For styli which are as likely to deflect in direction, such as star or ball shaped or in high speed scanning situations, more overtravel, to protect the probe from damage, is required. This gives more time between a deflection being registered and the
- 15 probe stopping than a probe which has reduced overtravel. In these circumstances, the insert which controls the return movement is more suitable.

- The kinematic locating elements described herein are
- 20 preferred and other formations may be used. Examples are given in 'Mechanical Design of Laboratory Apparatus' by H Braddick Chapman and Hall Ltd, London 1960.

- 25 The probes which have been described may be used in scanning or measuring objects for reproduction (co-ordinate measuring machine CMM) or measurement to check accuracy of a machining process (CMM or machine tool) or tool setting to account for tool wear when machining
- 30 an object. Thus, the probes may be spindle mounted and movable with respect to an object, or machine bed mounted and fixed with respect to an object, or mounted on an arm which can be removably located within the working volume of the machine (for example on a lathe).

1/4






Figure 5



PCT Application

GB0303863



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☒ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.